

LED LADDER LIGHTS

Dimming 10%–100%
3200K–5600K adjustable
High CRI>95
Manual and DMX control functions
12pcs T8 LED tube 80W for each one



4T22S

Model	Voltage	Power	Illuminance	Size	Weight
4T22S	AC 110-240V	960W	5240Lux/1m, 2510Lux/2m	H2.5M*W1.2M	10kg
				H8.2FT*W3.9FT	22lb

LED FRESNEL SPOT LIGHTS

Dimming 10%–100%
 3200K–5600K , 3200K or 5600K
 High CRI>95
 Manual and DMX control functions
 Self-cooling without fan , no noise
 AC or DC powered
 Pole-operation is available



200W

100W

Model	Voltage	Beam angle	Power	Illuminance	Dimension	Weight
100W	AC100-240V	15°-60°	100W	4600Lux/2m	300*400*518mm 11.8*15.8*20.4in	8.5kg 18.7lb
200W	DC 24V		200W	6800Lux/2m	300*480*518mm 11.8*18.9*20.4in	9.5kg 20.9lb

LED FRESNEL SPOT LIGHTS

Dimming 10%–100%
 3200K or 5600K
 High CRI>95
 Manual and DMX control functions
 Self-cooling without fan , no noise
 AC or DC powered



20W



50W



70W

Model	Voltage	Power	Beam angle	Illuminance	Dimension	Weight
20W	AC 100-240V DC 12V	20W	12°-50°	980Lux/2m	180*190*300mm	3kg
						7.1*7.5*11.8in
50W		50W		1800Lux/2m	180*230*370mm	5kg
					7.1*9.1*14.6in	11lb
70W		70W	11°-55°	3500Lux/2m	250*290*430mm	6.5kg
					9.8*11.4*16.9in	14.3lb

LED SOFT PANEL LIGHTS

Super natural soft lighting ; Manual and DMX control functions

Dimming 10%–100%

3200K–5600K , 3200K or 5600K

High CRI>95

AC or DC powered



60SP



120SP

Model	Voltage	Beam angle	Power	Illuminance	Dimension	Weight
60SP	AC100-240V DC 14.8V	120°	50W	1200Lux/1m	250*260*40mm 9.8*10.2*1.6in	2kg 4.4lb
120SP			100W	2100Lux/1m	420*260*80mm 16.5*10.2*1.6in	3kg 6.6lb

LED SOFT PANEL LIGHTS

Super natural soft lighting ; Manual and DMX control functions

Dimming 10%–100%

3200K–5600K , 3200K or 5600K

High CRI>95

AC or DC powered



100SP



190SP



Model	Voltage	Beam angle	Power	Illuminance	Dimension	Weight
100SP	AC100-240V	120°	90W	2400Lux/1m	290*290*65mm 11.4*11.4*2.6in	3kg 6.6lb
190SP			180W	4500Lux/1m	560*290*65mm 22*11.4*2.6in	5kg 11lb

LED SOFT LIGHTS

Super natural soft lighting ; Manual and DMX control functions

Dimming 10%–100%

3200K–5600K , 3200K or 5600K

High CRI>95

AC or DC powered



430SP



810SP



1190SP

Model	Voltage	Power	LED Bulbs	Illuminance	Dimension	Weight
430SP	AC 100-240V DC 14.8V	75W	400pcs	1000Lux/1m	420*420*50mm 16.5*16.5*2in	4.4kg 9.7lb
810SP		100W	600pcs	1650Lux/1m	800*420*50mm 31.5*16.5*2in	6.6kg 14.5lb
1190SP		120W	652pcs	1900Lux/1m	1180*250*50mm 46.5*9.8*2in	7.2kg 15.9lb

LED SOFT LIGHTS

Super natural soft lighting
 Dimming 10%–100%
 3200K–5600K, AC or DC powered
 High CRI>95



360SP



410SP



460SP



Model	Voltage	Power	LED Bulbs	Illuminance	Dimension	Weight
360SP	AC 100-240V DC 7.4V	45W	272pcs	950Lux/1m	250*440*42mm 9.8*17.3*1.7in	1.1kg 2.4lb
410SP		45W	384pcs	1050Lux/1m	250*440*42mm 9.8*17.3*1.7in	0.8kg 1.8lb
460SP		75W	400pcs	1150Lux/1m	450*55mm 17.7*2.2in	2.0kg 4.4lb

LED LIGHT KITS

Dimming 10%–100%
 3200K–5600K , 3200K or 5600K
 High CRI>95
 AC or DC powered



586p



810p



1030p

Model	Voltage	Power	LED Bulbs	Illuminance	Dimension	Weight
586p	AC 100-240V DC 7.4V	40W*3	576pcs*3	3100Lux/1m*3	230*230*25mm*3 9.1*9.1*1.0in*3	6.8kg 15lb
810p		48W*3	800pcs*3	3600Lux/1m*3	410*300*35mm*3 16.1*11.8*1.4in*3	9.8kg 21.6lb
1030p	AC 100-240V DC 14.8V	60W*3	1020pcs*3	5200Lux/1m*3	365*350*40mm*3 14.4*13.8*1.6in*3	14.5kg 32lb

LED PANEL LIGHTS

Manual and DMX control functions
 V / Anton mount Battery base available
 Dimming 10% - 100%
 3200K - 5600K, 3200K or 5600K
 High CRI > 95
 AC or DC powered



2044



610



1030



1510



MODEL	BEAM ANGLE	3 feet-lux					5 feet -Lux					6 feet-Lux					9 feet -Lux					LEDS/ POWER	Dimension	weight
		Bi-color (Temp)			5.6k	3.2k	Bi-color (Temp)			5.6k	3.2k	Bi-color (Temp)			5.6k	3.2k	Bi-color (Temp)			5.6k	3.2k			
		5.6k	4.7k	3.2kk			5.6k	4.7k	3.2kk			5.6k	4.7k	3.2kk			5.6k	4.7k	3.2kk					
610	30 Deg	2713	6006	2960			1130	2153	1087			721	1776	743			398	775	301			576pcs / 36W	300*300*50 mm / 11.8*11.8*1.9 in	2.4kg / 5.3lb
	45 Deg																							
	60 Deg				2530					1227					700						517			
1030	30 Deg																					576pcs / 36W	385*350*40 mm / 14.4*13.8*1.6 in	2.8kg / 6.2lb
	45 Deg																							
	60 Deg																							
1510	30 Deg																					576pcs / 36W	380*380*380 mm / 15.0*15.0*1.5 in	3.2kg / 7.1lb
	45 Deg																							
	60 Deg				8051				3315					2293							1249			
2044	30 Deg																					576pcs / 36W	540*330*48mm / 21.3*13.0*1.9 in	5.5kg / 12.1lb
	45 Deg																							
	60 Deg				11055				4542					3197							1593			